



SPH-75/8

Order No.: 10.2770

Price upon request

PRODUCTINFOS

Miniature hi-fi bass-midrange speaker, 15 W, 8 Ω

- Polypropylene cone
- Rubber surround
- Drilled pole core for an exceptionally high power capability
- For very small speaker systems, e.g. surround speakers

TECHNICAL SPECIFICATIONS

SPH-75/8

Impedance (Z)	8 Ω
Frequency range	f3-16,000 Hz
Resonant frequency (fs)	85 Hz
Power rating	15 W
Peak music power output	30 W
Sensitivity	83 dB/W/m

SPH-75/8

Suspension compl. (Cms)	1.3 mm/N
Moving mass (Mms)	2.7 g
Mech. Q factor (Qms)	3.9
Electr. Q factor (Qes)	0.65
Total Q factor (Qts)	0.56
Equivalent volume (Vas)	1.9 l
DC resistance (Re)	6.2 Ω
Force factor (BxL)	3.4 Tm
Voice coil induct. (Le)	0.15 mH
Voice coil diameter	20.5 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	± 0.75 mm
Eff. cone area (Sd)	32 cm ²
Magnet weight	150 g
Magnet diameter	$\varnothing 70$ mm
Mounting cutout	$\varnothing 72$ mm
Mounting depth	41.4 mm
Dimensions	78 x 78 x 42 mm
Width	78 mm
Height	78 mm
Depth	42 mm
Admiss. ambient temp.	0-40 °C
Weight	0.4 kg
Sales unit	1
Type of speaker	3"