



## SP-382PA

Order No.: 10.3320

**Price upon request**

### PRODUCTINFOS

**Universal bass speaker, 150 W, 8  $\Omega$**

For bass applications, also in power speaker systems.

### TECHNICAL SPECIFICATIONS

#### SP-382PA

Impedance (Z)	8 $\Omega$
Frequency range	f3-4,000 Hz
Resonant frequency (fs)	25 Hz
Power rating	150 W
Peak music power output	300 W
Sensitivity	94 dB/W/m
Suspension compl. (Cms)	0.26 mm/N
Moving mass (Mms)	73 g
Mech. Q factor (Qms)	3.03

**SP-382PA**

Electr. Q factor (Qes)	0.99
Total Q factor (Qts)	0.75
Equivalent volume (Vas)	270 l
DC resistance (Re)	7.0 $\Omega$
Force factor (BxL)	10.87 Tm
Voice coil induct. (Le)	0.8 mH
Voice coil diameter	$\varnothing$ 50 mm
Voice coil former	aluminium
Linear excursion ( $X_{MAX}$ )	$\pm 3.5$ mm
Eff. cone area (Sd)	825 cm <sup>2</sup>
Magnet weight	1.2 kg
Magnet diameter	$\varnothing$ 142 mm
Mounting cutout	$\varnothing$ 355 mm
Mounting depth	139 mm
Dimensions	$\varnothing$ 385 mm x 150 mm
Outside diameter	$\varnothing$ 385 mm
Width	$\varnothing$ 385 mm
Depth	150 mm
Admiss. ambient temp.	0-40 °C
Weight	3.9 kg
Sales unit	1
Type of speaker	15"