

NDV8401

Mediamatics NDV8401 DVD on a Chip Processor



Literature Number: SNOS929B

Mediamatics™ NDV8401 DVD on a Chip Processor

Platform

The Mediamatics™ NDV8401 DVD on a Chip Processor provides features and cost effective system integration for Universal DVD Players and Internet connected Players/Recorders. Integration of an industry standard RISC processor architecture operating at high performance levels allows system developers to combine the ease of C based application coding with flexible system extensions unavailable in other platforms. This processor can be equally applied to DVD-Video & DVD-Audio playback and Internet Appliance products.

quality and flexibility with wide ranging support for all common disc-based audio formats and many Internet based formats. A custom 24-bit DSP has been developed to provide a powerful solution for the latest compute intensive audio algorithms. Support includes DVD-Video, VideoCD and CD formats. The flexible audio structure allows audio data to originate from disc-based media, external digital audio streams or via the Internet. Full 5.1 channel output with simultaneous 2-channel down-mix and IEC958/1937 output is standard for the NDV8401.

Audio

The NDV8401 provides unsurpassed audio processing

Features

The NDV8401 is a “system on silicon” solution for consumer DVD Players. Significant feature enhancements are being provided on this version of the NDV8401 device to address both full-featured DVD-Players and DVD-R/W Recorder/Player products.

System Solution

- Designed for DVD Players with the capability to play DVD-Video, DVD-Audio, VideoCD 2.0, CD-DA, CD-DA in DTS format, and CD-DA with CD-TEXT content
- Unified Memory Architecture (UMA) allows sharing of single memory pool for instruction fetch, execution space, system stream demux, video decode, audio decode, video display and audio presentation
- Primary clock operating frequency range between 80 – 100MHz based on feature/power requirements
- Three on-chip PLLs/Frequency Synthesizers which can generate all required system clocks
- Design optimized for 16Mbit & 64Mbit SDRAM operation
- Flexible host bus, communication ports & DVD Front-End control to support all DVD system elements

Integrated RISC Processor

- 32-bit processor with an operating frequency of 67.5 MHz
- 2KB instruction cache
- 1KB data cache
- 1KB local RAM

DVD Front End Interface

- Supports DVD format, Video CD 2.0 (White Book), & CD-DA (Red Book)
- Real time error detection & correction
- Supports serial data input with sync search, descrambling, EDC, & serial to parallel formatting blocks
- Supports 8-bit parallel data input with selectable bypass of the internal Front End processing blocks
- Integrated CSS decryption/descrambling for DVD content

MPEG Transport Engine

- Accepts input from front end at up to 40Mbps+
- Program Stream demultiplexing
- Sub-stream header parsing for DVD

MPEG Video Decode

- Decodes MPEG1 video & MPEG2 main level, main profile video (720x576)
- Maximum input bit-rate of 15 Mbits/sec

MPEG & Dolby Audio

- Custom DSP design optimized for processing of DVD audio formats
- Provides 6 channel PCM outputs + simultaneous 2 channel stereo downmixed PCM outputs
- Decodes MPEG1 & 2 stereo formats
- Decodes Dolby Digital (Dolby AC-3) audio up to 5.1 channels
- Audio down sampling option for Dolby Digital
- support for all DVD PCM audio formats including 96KHz sampling rate
- Flexible interface for multiple audio DACs for 16/18/20/24 bit formats
- Integrated SPDIF encoding capability for both IEC958 & IEC1937 formats
- Support for MPEG-2 multi-channel extensions & DTS encoded material via SPDIF output
- Simultaneous SPDIF output with analog DAC output
- Integrated Karaoke audio capture port & digital mixing
- Audio Frequency Synthesizer to support multiple audio sampling rates for AudioCD, VideoCD, & DVD

Video/Graphics Processor

- 2-tap vertical filter/scaler, 8-tap horizontal filter/scaler for MPEG-1 scaling & sinx/x DAC upsampling
- YUV 4:2:0 input format with vertical filter for chroma conversion to 4:4:4
- Pan & Scan for 16:9 to 4:3 output conversion & pass-through letterbox
- Sub-Picture decoder with Alpha Blending for DVD SPUs
- 2/4/8 bit full screen OSD functions with alpha blending for flexible graphics display
- Up to 8 regions per line
- Closed caption support

NTSC/PAL Encoder

- NTSC-M, PAL-M/B/D/G/H/I
- Composite, S-Video & YCrCb component video outputs
- Teletext encoder with sequencer & filter
- Wide Screen Signalling in encoder for PAL formats
- Copy Generation Management System in NTSC/PAL encoder for both NTSC & PAL formats
- 4 field NTSC or 8 field PAL generation
- Luminance Filtering with 2x oversampling and sinx/x correction
- Chrominance Filtering with 4 times oversampling
- 3 10-bit DACs
- Macrovision Copy Protection Version 7.01

Communication Ports

- Flexible serial port communication combinations
- 2 integrated USARTs
- 2 integrated Synchronous Serial Ports
- Sharing of pins via 3 different modes that allow designer to choose the configuration of serial ports
- Integrated Consumer Infrared demodulator in one UART

Design for Test

- Full scan methodology

Low cost manufacturing

- 3.3V, 0.35?, 4-layer metal single polycide standard cell National Semiconductor technology
- 208 pin MQUAD package

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
Americas
Tel: 1-800-272-9959
Fax: 1-800-737-7018
Email: support@nsc.com
www.national.com

National Semiconductor Europe

Fax: +49 (0) 180-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Français Tel: +33 (0) 1 41 91 8790

National Semiconductor Asia Pacific Customer Response Group

Tel: 65-2544466
Fax: 65-2504466
Email: ap.support@nsc.com

National Semiconductor Japan Ltd.

Tel: 81-3-5639-7560
Fax: 81-3-5639-7507

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Mobile Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Transportation and Automotive	www.ti.com/automotive
Video and Imaging	www.ti.com/video

TI E2E Community Home Page

e2e.ti.com

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2011, Texas Instruments Incorporated