

New Jersey Semiconductor Products, Inc.

20 STERN AVE.
SPRINGFIELD, NEW JERSEY 07081
U.S.A.

2N2903
2N2903A

TELEPHONE: (973) 376-2922
(212) 227-6005
FAX: (973) 376-8960

NPN SILICON DUAL TRANSISTOR

JEDEC TO-78 CASE

MAXIMUM RATINGS ($T_A=25^\circ\text{C}$ unless otherwise noted)

	SYMBOL		UNIT
Collector-Base Voltage	V_{CB0}	60	V
Collector-Emitter Voltage	V_{CE0}	30	V
Emitter-Base Voltage	V_{EB0}	7.0	V
Collector Current	I_C	50	mA
Power Dissipation (One Die)	P_D	200	mW
Power Dissipation (Both Dice)	P_D	300	mW
Power Dissipation (One Die, $T_C=25^\circ\text{C}$)	P_D	600	mW
Power Dissipation (Both Dice, $T_C=25^\circ\text{C}$)	P_D	1200	mW
Operating and Storage Junction Temperature	T_J, T_{STG}	-65 TO +200	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
I_{CB0}	$V_{CB}=50\text{V}$		0.01	μA
I_{CB0}	$V_{CB}=50\text{V}, T_A=150^\circ\text{C}$		15	μA
I_{EB0}	$V_{BE}=5.0\text{V}$		0.01	μA
BV_{CB0}	$I_C=10\mu\text{A}$	60		V
BV_{CE0}	$I_C=10\text{mA}$	30		V
BV_{EB0}	$I_E=0.1\mu\text{A}$	7.0		V
$V_{CE}(\text{SAT})$	$I_C=5.0\text{mA}, I_B=0.5\text{mA}$		1.0	V
$V_{BE}(\text{SAT})$	$I_C=5.0\text{mA}, I_B=0.5\text{mA}$		0.9	V
h_{FE}	$V_{CE}=5.0\text{V}, I_C=10\mu\text{A}$	60	-	
h_{FE}	$V_{CE}=5.0\text{V}, I_C=10\mu\text{A}, T_A=-55^\circ\text{C}$	25	-	
h_{FE}	$V_{CE}=5.0\text{V}, I_C=1.0\text{mA}$	125	625	
h_{FE}	$V_{CE}=5.0\text{V}, I_C=1.0\text{mA}, T_A=-55^\circ\text{C}$	60	-	
f_T	$V_{CE}=10\text{V}, I_C=5.0\text{mA}, f=30\text{MHz}$	60		MHz
C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=140\text{kHz}$		8.0	pF
C_{ib}	$V_{BE}=0.5\text{V}, I_C=0, f=140\text{kHz}$		10	pF
NF	$V_{CE}=5.0\text{V}, I_C=10\mu\text{A}, R_S=10\text{k}\Omega, f=1.0\text{kHz}$		7.0	dB
h_{FE1}/h_{FE2}	$V_{CE}=5.0\text{V}, I_C=1.0\text{mA}$ (2N2903)	0.80	1.0	
h_{FE1}/h_{FE2}	$V_{CE}=5.0\text{V}, I_C=1.0\text{mA}$ (2N2903A)	0.90	1.0	
$ V_{BE1}-V_{BE2} $	$V_{CE}=5.0\text{V}, I_C=10\mu\text{A}$ (2N2903)	-	10	mV
$ V_{BE1}-V_{BE2} $	$V_{CE}=5.0\text{V}, I_C=10\mu\text{A}$ (2N2903A)	-	5.0	mV
$\Delta(V_{BE1}-V_{BE2})$				
ΔT_A	$V_{CE}=5.0\text{V}, I_C=10\mu\text{A}, T_A=-55 \text{ TO } +125^\circ\text{C}$ (2N2903)		20	$\mu\text{V}/^\circ\text{C}$
$\Delta(V_{BE1}-V_{BE2})$				
ΔT_A	$V_{CE}=5.0\text{V}, I_C=10\mu\text{A}, T_A=-55 \text{ TO } +125^\circ\text{C}$ (2N2903A)		10	$\mu\text{V}/^\circ\text{C}$



NJ Semi-Conductors reserves the right to change test conditions, parameters limits and package dimensions without notice information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.